



REVISION	DESCRIPTION	REVISED BY	TOLERANCES		ANGLE 1/2°	SCALE	UNIT	PART NAME	PART NO	DWG NO
			DRAWN BY	CHECKED BY						
△2010.06.08	依客人(貴高) 要求增加端子寬度尺寸	楊偉韶	郭洋			5/4	mm	KR SPEC DRAWING		S1094E
△2009.02.26	依總表修改品名由KR-203A改為KR-203A-7	楊偉韶								
△2006.01.12	修改視圖位置, 重新出圖	楊紹才								
△2012.07.09	整理圖面, 重新出圖	郭洋						KR-203A-7	3	

- SPECIFICATION MODEL: KR-203A-7**
- RATING: 2.5A 250VAC  
 INSULATION RESISTANCE: 100Mohm, DC 500V  
 DIELECTRIC STRENGTH: 3000VAC FOR 1 MINUTE  
 MEET UL 498 & IEC/EN60320 REQUIREMENTS
- NOTES:  
 1. MATERIAL: NYLON66 94V-0.  
 2. PIN TO PIN MUST WITHSTAND 3KVAC IN 1 MINUTE MIN.  
 3. TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.3mm