



NOTE:
 1. MATERIAL: NAN YA 1403G3,PBT WITH 15%GF,UL 94V-0
 2. TOLERANCES UNLESS OTHERWISE SPECIFIED:±0.012 (in/mm)

△ SPECIFICATION MODEL: KS-101
 △ RATING: 15A 250VAC (UL/ CUL)
 10A 250VAC (ENEC15/CUL)
 △ INSULATION RESISTANCE: 100MΩ MIN, DC 500V
 △ DIELECTRIC STRENGTH: 3000VAC FOR 3 SECONDS
 MEET UL 498 & IEC/EN60320 REQUIREMENTS

REVISION	DESCRIPTION	REVISED BY	TOLERANCES		ANGLE		SCALE	UNIT	PART NAME	PART NO	KS SPEC DRAWING	DWG NO
			DRAWN BY	CHECKED BY	DESIGNED BY	APPROVED BY						
△2018.09.28	增加刻字圖面	楊偉部	梁春林	梁春林	1/1	mm	KS-101	S0298H				
△2011.05.17	取消四圍安規,新增ENEC,整理資料,重新出圖	胡曦	楊偉部	楊偉部								
△2010.01.20	修訂耐壓,由2000V改為3000V	楊偉部	楊偉部	楊偉部								
△2009.11.30	重新整理出圖	楊偉部	楊偉部	楊偉部								