C2-3013 LED Work Light

10-33VDC | Wide Beam | 11,200lm | 57W | IP68 / 69K



Designed for:


Off road & Specialist Vehicles

Agriculture & Construction


The C2-3013 is a heavy-duty LED light bar designed for off-road applications. It features an aluminium housing and a polycarbonate lens, with sixteen 5W LEDs providing an effective output of 2700lm of bright and uniform floodlight illumination. Operating within a voltage range of 10-33VDC, it ensures reliable lighting with low 57W energy usage. The light bar is designed to withstand harsh conditions, with an IP68/IP69K rating for protection against dust, water, and chemicals, and it offers excellent shock resistance. Approved under ECE R10 and ISO 13766, it meets international standards for electromagnetic compatibility. It has sturdy end brackets with four-screw mounting points to ensure extra stability. The LEDs emit a cool white light, enhancing visibility in low-light conditions. This light bar is ideal for use in off-road, specialist, agricultural, and construction vehicles. Overheat, reverse polarity and over voltage protected

10-33VDC **Wide Beam** **11,200lm** **57W** **IP68 / 69K**

Dimensions (mm)



Beam Pattern 2.5m at 10°



Specifications

Housing Shape	Light Bar	Beam Pattern	Flood
Raw Lumen Output	11,200lm	Effective Lumen Output	2700lm
Colour Temperature	5700K	Voltage	10-33VDC
Nominal Current at	4.72A@12V ~ 2.17A@24V	Power Consumption	57W
IP Rating	IP68 / IP69K	Shock Resistance	10G
Operating Temp Range	-30°C...+65°C	Housing Material	Aluminium
Lens Material	Polycarbonate	Dimensions	547.6 x 86.8 x 83.2mm
Mounting Style	Double bracket 4 bolt mount	Termination	Deutsch DT04-2P connector
EMC	ECE R10, ISO13766	Approvals	-

Lucid Electronics Limited is an appointed SCI sales agent
Unit 425 Bedford Heights, Manton Lane, Bedford, MK41 7PH | Company Number 10385887 | VAT 262 6152 16
UK Office: +44 (0)1234 380226 | France Office: +33 (0) 7 67 38 35 67 | Email info@lucidelectronics.com | web: www.lucidelectronics.com