

SLM23 Series

IP68 Self Locking Plug & Sockets

The compact SL series IP68 self locking connectors feature a quick push to lock, and twist to release design for rapid installation. They come in plug and socket configurations for inline cable and panel mounting, are waterproof, dustproof and UV-resistant for demanding industrial and outdoor environments. They are well suited for use in lighting, agricultural, renewable energy, robotics, automation, industrial and applications. The wider product family also includes M15, M19, M25 and SLP screwless connection types cable to cable and cable to panel.



- 2 to 5 pin Gold plated contacts for power and signal
- Supplied as mating pairs for value and convenience
- IP68 when mated (IP65 with cap)
- PA66 UV and flame retardant material
- Screw and solder options up to 30A / 450V
- Cable, front panel, rear panel and flange mount types
- Dust cap included with panel mount types
- Cable range 5 - 12mm for up to 4.0mmsq wire
- Quick push to connect, twist to release - anti-vibration
- UL, cUL, TUV, CE approvals

Specifications & Materials:

Unit of Supply	Male & Female pair (Panel / Flange & silicon dust cap)
Number of Pins	2 / 3 / 4 / 5
Connection Type	Screw or Solder
IP Rating	IP68 when mated (IP65 panel with dust cap)
Voltage	450V
Current Rating	30A (2 / 3 pin) / 16A (4 / 5 pin)
Wire Size	0.5-4.0 mm ² (2 / 3 pin) / 0.5-2.5 mm ² (4 / 5 pin)
Mating Cycles	1500
Material	PA66 UV and Flame retardant plastic
Panel Cutout	Front 25.1mm / Rear 20.5mm
Cable Diameter	5 - 12 mm
Temperature Rating	-40°C to +105°C
ROHS Status	Compliant
Approvals	UL, ENEC, CE

SLM23 Series

IP68 Self Locking Plug & Sockets

Material Types & Configurations

Cable to Cable




Cable to Flange




Cable to Panel




Cable to Cable (male)




Cable to Cable (female)



Front Panel / Rear Panel



Flange Socket



SLM23 Series

IP68 Self Locking Plug & Sockets

Part Number Configurator

Series:	SLM23	Example:	SLM23	02P	F	SC	1
Number of Pins:	02P - 2 pins 05P - 5 pins 03P - 3 pins 04P - 4 pins						
Mounting Type:	C - Cable F - Flange P - Rear Panel R - Front Panel						
Connection Type:	SC - Screw SO - Solder						
Polarity:	0 - Female panel & male cable 1 - Female cable & male panel						

SLM23-02PF-SC-1 - SLM23 2 pin flange mount screw female cable male panel

Also available

SLP Screwless



SLM15



SLM19

