

LVF Series

Vertical Float Switch Level Sensors

LVF Series vertical liquid level sensors, also called fluid sensor or float switch, are mechanical devices that monitor liquid levels inside a container. In typical applications, a vertical liquid level sensor triggers an action, or warning, when the liquid reaches a certain level. The sensors are made up of two main components: a center tubed float and a reed switch, both operated by magnets. When the float reaches a predetermined level, the reed switch reacts by closing or opening a circuit. These types of sensors are often used in appliance, industrial liquid / storage tank monitoring, HVAC and fluid management applications.



- No standby power required
- Compact and robust construction
- High consistency and long electrical lifespan
- -40°C to 160°C temp range (material-dependent)
- Multiple float and stem materials available
- Vertical mounting design
- Custom stem lengths, cable types and threads available (MOQ dependent)
- High voltage option up to 1000V

Specifications & Materials:

Sensor Type	Float / Level
Orientation	Vertical (Float Up or Down)
Stem Material	Plastic (PA/PP) / Metal (Stainless Steel)
Float Material Options	PP (Water / Dilute Acids) / PA (Oil) / NBR (Gasoline) / SS (High Temp)
Recommended Liquid Density	$\geq 0.75 \text{ g/cm}^3$
Float Specific Gravity (Typical)	0.65 - 0.85 (Material Dependent)
Ingress Protection	IP67
Mounting Thread	Metric / BSP / NPT
Number Of Switch Points	1 / 2 / 3...
Switch	Normally Open (NO) / Normally Closed (NC) / Changeover (CO)
Operating Temperature Range	-20°C to +80°C (Plastic) / -40°C to +160°C (Stainless Steel)
Hysteresis	2mm - 6mm Typical
Vibration Resistance	20g
Shock Resistance	50g
Cable Material	PVC (Standard) / Teflon (Optional)
ROHS Status	Compliant

LVF Series

Vertical Float Switch Level Sensors

Electrical Specifications:

	Low Voltage	High Voltage
Rated Power	10W	100W
Switch Voltage	180V	1000V
Switch Current	0.5A	1A
Carry Current	1.25A	2.5A
Contact Resistance	150mΩ	
Insulation Resistance	≥100 MΩ @ 500VDC	
Dielectric Strength	1500VAC / 60s	2500VAC / 60s
Electrical Life	≥1 x 10 ⁵ Operations (Resistive Load)	

Part Number Configurator:*

Series:	LVF	Example:	LVF	A	1	1	3	52	NO	L	35	
Material Type:	A - Polypropylene (PP) D - Polyvinyl Chloride (PVC) B - Polyphenylene Sulfide (PPS) E - Stainless SUS304 C - Polyamide (PA) F - Stainless SUS316											
Switch Points:	1 / 2 / 3 etc.											
Floats:	1 / 2 / 3 etc.											
Thread:	1 - M6	4 - M12	7 - 1/2NPT									
	2 - M8	5 - M16	8 - 1/8BSP									
	3 - M10	6 - 1/8NPT	9 - G1/2BSP									
Arm Length (mm):	xxx											
Switch Output:	NO - Normally Open		NC - Normally Closed		CO - Changeover							
Voltage:	L - Low Voltage		H - High Voltage									
Cable Length (mm):	xxx											

LVFA113-52-NOL-35 : Vertical Float Switch, Polypropylene, 1 Switch Point, 1 Float, M10 Thread, 52mm Arm, Normally Open, Low Voltage, 35mm Cable

*All options available on request, MOQ dependent.
Please contact us with your requirements for more details.


LVF Series

Vertical Float Switch Level Sensors

Dimensional Examples:

Part Number	Cable Length (C mm)	Float Diameter (D mm)	Stem Length (L mm)	Thread Size (M)	Switch Point 1 (S1 mm)	Switch Point 2 (S2 mm)
LVFD114-65-NOL-50	500	24	65	M12	26	-
LVFD118-65-NOL-100	1000	24	65	1/8 BSP	26	-
LVFA113-52-NOL-35	350	24	52	M10	17.5	-
LVFA113-73-NOL-35	350	24	73	M10	25	-
LVFA113-94-NOL-35	350	28	94	M10	25	-
LVFA213-115-NOL-30	300	28	115	M10	30	75

LVF Dimensions




LVF Series


Vertical Float Switch Level Sensors

Application Notes / Examples:

Single Float Switch




Double Float Switch



Also available

LHF Float Switch (Plastic)



LHF Float Switch (Stainless)



LHVF Float Switch

